



REV. B - SIC - 7/29/2020 - UPDATED ANNOTATIONS; UPDATED WEIGHT RATING TO MAX H-40, WAS H-20; ADDED SOIL BEARING PRESSURES; 1/4" CABLE CLIP INSERT QTY: 2, WAS QTY: 1









MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD DEPENDENT ON TRENCH COVER RATING MINIMUM ALLOWABLE SOIL BEARING PRESSURE – H-40: 5,500 PSF; H-20: 3,000 PSF

## DRAWN BY: ROBIN FLINT

CREATED DATE: 3/21/2011 REVISION LEVEL: B
SAVED DATE: 7/29/2020 SAVED BY: scallahan

**WEIGHT:** 

838 LBS.

MATERIAL: CONCRETE



DESCRIPTION:

## HT CHANNEL; 45 DEG. ANGLE

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL: ± 1/8"
ANGULAR: ± 2°

CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094

SHEET 1 OF 1

PART NUMBER:

801016HT 45L