



MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD
 DEPENDENT ON TRENCH COVER RATING
 MINIMUM ALLOWABLE SOIL BEARING PRESSURE - H-40: 4,000 PSF; H-20: 3,000 PSF

| | |
|--------------------------------|----------------------------|
| DRAWN BY: ROBIN FLINT | |
| CREATED DATE: 3/21/2011 | REVISION LEVEL: A |
| SAVED DATE: 8/11/2020 | SAVED BY: scallahan |
| WEIGHT: 1116 LBS. | MATERIAL: CONCRETE |

1010 NORTH STAR DRIVE
 P.O. BOX 69
 ZUMBROTA, MN 55992-0069

| | | |
|----------------------------------|----------------------------|--------------|
| DESCRIPTION: | | SHEET 1 OF 1 |
| HT CHANNEL; 45 DEG. ANGLE | | |
| DIMENSIONS ARE IN INCHES | CONTACT INFORMATION: | |
| TOLERANCES: | EMAIL: INFO@CONCASTINC.COM | |
| FRACTIONAL: ± 1/8" | PHONE: (507) 732-4095 | |
| ANGULAR: ± 2° | FAX: (507) 732-4094 | |
| PART NUMBER: | | |
| 802024HT 45R | | |