GALV. STEEL TOP RAILS 0 SOLID BOTTOM 48" (29") STEEL REINFORCED CONCRETE Ø1/2"-13 UNC LIFTING INSERT (4X) 10 ∈ 2" – Ø 1/4" INSERT FOR CABLE CLIP (2X) 15" - 12" -> 3" 16" 22" Π ጉ ü ш AASHTO H-20 RATED - 32,000 LB. SINGLE AXLE LOAD DESCRIPTION Т 4 ~ D

DRAWN BY: ROBIN	FLINT			C CHANNEL - 45 A	
CREATED DATE: 7/28/	2015 REVISION LEVEL: B	CONCAST	DIMENSIONS ARE IN INCHES	CONTACT INFORMATION:	NGLE
SAVED DATE: 10/9/	2019 SAVED BY: scallahan	1010 NORTH STAR DRIVE	FRACTIONAL: ± 1/8"	EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095	SHEET 1 OF 1
WEIGHT:	MATERIAL:	$P \cap B \cap X 69$	ANGULAR: ± 2°	FAX: (507) 732-4094	
592 LBS. CONCRETE		ZUMBROTA, MN 55992-0069	PART NUMBER: HT1216 45R		

REV. A - RLF - 6/7/2016 - 1" INTERLOCK RELIEF WAS A 7/8" PROTRUSION. REV. B - SIC - 10/9/2019 - 1/2"-13 UNC LIFTING INSERTS QTY: 4, WAS QTY: 2; REMOVED NOTE 1; ADDED CABLE CLIP NOTATION