



MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD  
 DEPENDENT ON TRENCH COVER RATING  
 MINIMUM ALLOWABLE SOIL BEARING PRESSURE - H-40: 5,500 PSF; H-20: 3,000 PSF

|                                |                            |
|--------------------------------|----------------------------|
| <b>DRAWN BY: ROBIN FLINT</b>   |                            |
| <b>CREATED DATE: 3/21/2011</b> | <b>REVISION LEVEL: B</b>   |
| <b>SAVED DATE: 8/24/2020</b>   | <b>SAVED BY: scallahan</b> |
| <b>WEIGHT: 838 LBS.</b>        | <b>MATERIAL: CONCRETE</b>  |



**CONCAST**  
 1010 NORTH STAR DRIVE  
 P.O. BOX 69  
 ZUMBROTA, MN 55992-0069

|                                  |                            |              |
|----------------------------------|----------------------------|--------------|
| <b>DESCRIPTION:</b>              |                            | SHEET 1 OF 1 |
| <b>HT CHANNEL; 45 DEG. ANGLE</b> |                            |              |
| DIMENSIONS ARE IN INCHES         | CONTACT INFORMATION:       |              |
| TOLERANCES:                      | EMAIL: INFO@CONCASTINC.COM |              |
| FRACTIONAL: ± 1/8"               | PHONE: (507) 732-4095      |              |
| ANGULAR: ± 2°                    | FAX: (507) 732-4094        |              |
| <b>PART NUMBER:</b>              |                            |              |
| <b>HT6F1016 45R</b>              |                            |              |