



REV. B - SIC - 8/25/2020 - UPDATED ANNOTATIONS; UPDATED WEIGHT RATING NOTE; ADDED SOIL BEARING PRESSURES; UPDATED PART NUMBER









**NOTE 1:** FOR NON-STANDARD LENGTHS THE CHANNEL WILL BE SOLID BOTTOM AND DESIGNATED WITH ITS CORRESPONDING LENGTH MEASUREMENT. IE: HT6F2016 32"

MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD DEPENDENT ON TRENCH COVER RATING MINIMUM ALLOWABLE SOIL BEARING PRESSURE – H-40: 4,000 PSF; H-20: 3,000 PSF

## DRAWN BY: ROBIN FLINT

CREATED DATE: 4/1/2011 REVISION LEVEL: B
SAVED DATE: 8/25/2020 SAVED BY: scallahan

WEIGHT: MATERIAL:

1185 LBS. CONCRETE



1010 NORTH STAR DRIVE P.O. BOX 69 ZUMBROTA, MN 55992-0069

## DESCRIPTION:

## **HEAVY TRAFFIC CHANNEL**

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL: ± 1/8"
ANGULAR: ± 2°

CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094

SHEET 1 OF 1

PART NUMBER:

HT6F2016 48"