



**NOTE 1:** FOR NON-STANDARD LENGTHS THE CHANNEL WILL BE SOLID BOTTOM AND DESIGNATED WITH ITS CORRESPONDING LENGTH MEASUREMENT. IE: HT6F3016 32"

MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD  
DEPENDENT ON TRENCH COVER RATING  
MINIMUM ALLOWABLE SOIL BEARING PRESSURE - H-40: 3,000 PSF; H-20: 3,000 PSF

<b>DRAWN BY: SAMUEL CALLAHAN</b>	
<b>CREATED DATE:</b> 4/1/2011	<b>REVISION LEVEL:</b> A
<b>SAVED DATE:</b> 8/25/2020	<b>SAVED BY:</b> scallahan
<b>WEIGHT:</b> 1311 LBS.	<b>MATERIAL:</b> CONCRETE

1010 NORTH STAR DRIVE  
P.O. BOX 69  
ZUMBROTA, MN 55992-0069

<b>DESCRIPTION:</b> <b>HEAVY TRAFFIC CHANNEL</b>		SHEET 1 OF 1
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ± 1/8" ANGULAR: ± 2°	CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094	
<b>PART NUMBER:</b> <b>HT6F3016 48"</b>		