



NOTE 1: FOR NON-STANDARD LENGTHS THE CHANNEL WILL BE SOLID BOTTOM AND DESIGNATED WITH ITS CORRESPONDING LENGTH MEASUREMENT. IE: HTF1012 32"

MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD
 DEPENDENT ON TRENCH COVER RATING
 MINIMUM ALLOWABLE SOIL BEARING PRESSURE - H-40: 5,000 PSF; H-20: 3,000 PSF

| | |
|--------------------------------|----------------------------|
| DRAWN BY: ROBIN FLINT | |
| CREATED DATE: 3/21/2011 | REVISION LEVEL: B |
| SAVED DATE: 7/2/2020 | SAVED BY: scallahan |
| WEIGHT: 768 LBS. | MATERIAL: CONCRETE |

1010 NORTH STAR DRIVE
 P.O. BOX 69
 ZUMBROTA, MN 55992-0069

| | | |
|-------------------------------------|--|--------------|
| DESCRIPTION: | | SHEET 1 OF 1 |
| HEAVY TRAFFIC CHANNEL | | |
| DIMENSIONS ARE IN INCHES | CONTACT INFORMATION: | |
| TOLERANCES: | EMAIL: INFO@CONCASTINC.COM | |
| FRACTIONAL: ± 1/8" ANGULAR: ± 2° | PHONE: (507) 732-4095 FAX: (507) 732-4094 | |
| PART NUMBER: | | |
| HTF1012SB 48" | | |