



REV. A - SIC - 7/13/2020 - UPDATED WEIGHT RATING TO MAX H-40, WAS H-20; ADDED SOIL BEARING PRESSURES









MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD DEPENDENT ON TRENCH COVER RATING MINIMUM ALLOWABLE SOIL BEARING PRESSURE – H-40: 3,000 PSF; H-20: 3,000 PSF

DRAWN BY: ROBIN FLINT

CREATED DATE: 3/21/2011 REVISION LEVEL: A
SAVED DATE: 7/13/2020 SAVED BY: scallahan

**WEIGHT:** 

962 LBS.

MATERIAL: CONCRETE



1010 NORTH STAR DRIVE P.O. BOX 69 ZUMBROTA, MN 55992-0069

## DESCRIPTION:

## HT CHANNEL; 22.5 DEG. ANGLE

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ± 1/8" ANGULAR: ± 2° CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094

SHEET 1 OF 1

PART NUMBER:

HTF2416 22.5R