



**NOTE 1:** FOR PVC SIZES SMALLER THAN 4", USE CONCAST RC41 (REDUCING COUPLER).

**NOTE 2:** FOR ADDED SECURITY, PENTA HEAD (P/N: PTA.38-1.5) OR SURELOCK BOLTS (P/N: SL.38-1.25) CAN BE ADDED

AASHTO H-20 RATED – 32,000 LB. SINGLE AXLE LOAD

<b>DRAWN BY: NATHAN KOPPINGER</b>		 1010 NORTH STAR DRIVE P.O. BOX 69 ZUMBROTA, MN 55992-0069	<b>DESCRIPTION:</b>		
<b>CREATED DATE:</b> 1/12/2023	<b>REVISION LEVEL:</b> A		<b>PULL BOX W/ GALV. STEEL COVERS</b>		
<b>SAVED DATE:</b> 11/8/2023	<b>SAVED BY:</b> scallahan		DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: $\pm 1/8$ " ANGULAR: $\pm 2^\circ$	CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094	SHEET 1 OF 1
<b>WEIGHT:</b> 10416 LBS.	<b>MATERIAL:</b> NOTED		<b>PART NUMBER:</b> PB9-60-108-48-SPA		