


HINGED COVER W/ TREAD PLATE  
P/N: 40-43-HALT-2




HEX BOLTS SUPPLIED BY  
COVER MANUFACTURER  
P/N: HHB.38-2.5 (2X)

ALUMINUM ID PLATE  
"CONCAST"  
P/N: LTR-ID



HINGED COVER W/ TREAD PLATE  
P/N: 40-43-HALT-1

40-86-FRM-HALT  
BOLT DOWN FRAME



**NOTE 1:** FOR ADDED SECURITY, PENTA HEAD (P/N: PTA.38-2.5) OR SURELOCK BOLTS (P/N: SL.38-2.5) CAN BE ADDED

AASHTO H-10 RATED – 16,000 LB. SINGLE AXLE LOAD

DRAWN BY: <b>JESSE GUTTING</b>	
CREATED DATE: <b>6/11/2019</b>	REVISION LEVEL: <b>A</b>
SAVED DATE: <b>3/27/2020</b>	SAVED BY: <b>jgutting</b>
WEIGHT: <b>236 LBS.</b>	MATERIAL: <b>WELDED ALUMINUM</b>



**CONCAST**  
1010 NORTH STAR DRIVE  
P.O. BOX 69  
ZUMBROTA, MN 55992-0069

DESCRIPTION: <b>ALUMINUM HINGED COVER</b>		SHEET 1 OF 2
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ± 1/8" ANGULAR: ± 2°	CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094	
PART NUMBER: <b>40-86-HALT</b>		