



- NOTE 1:** USED FOR COSMETIC REPAIRS - 3" X 6" PATCH
- NOTE 2:** KIT INCLUDES PATCH & INSTRUCTIONS
- NOTE 3:** HARDENS UNDER UV LIGHT WITHIN 10 TO 60 MINUTES
- NOTE 4:** PATCH CAN BE DRILLED, SANDED OR PAINTED AFTER FULLY CURED.
- NOTE 5:** CONCAST RECOMMENDS CLEANING CRACKED SURFACE WITH ACETONE PRIOR TO PATCH APPLICATION FOR BETTER ADHESION
- NOTE 6:** SHELF LIFE IS 1.5 YEARS
- NOTE 7:** SEE WEB FOR TECHNICAL SPECS IN BROCHURE. www.concastinc.com/product_specs/Catalogs/PatchKwik_Brochure_web.pdf

DRAWN BY: ROBIN FLINT		 1010 NORTH STAR DRIVE P.O. BOX 69 ZUMBROTA, MN 55992-0069	DESCRIPTION: SELF ADHESIVE REPAIR PATCH		
CREATED DATE: 7/1/2009	REVISION LEVEL: A		DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ± 1/8" ANGULAR: ± 2°	CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094	SHEET 1 OF 1
SAVED DATE: 8/12/2020	SAVED BY: jgutting		PART NUMBER: PK-36		
WEIGHT: .1 LBS.	MATERIAL: -				